

# SHRINE 3.0.0 Chapter 6 - Install | Configure a Database Service

SHRINE uses MariaDB by default. SHRINE supports MS SQL and Oracle as well. Best practices for databases recommend a separate database server with backups and fail-overs. Many institutions have policies which require that configuration. That said SHRINE's database needs are modest enough to run MariaDB on the same operating system.

A minimal SHRINE system will need to install MariaDB. For more information on MariaDB, please visit: <http://mariadb.org/> . The procedure is:

```
$ sudo yum -y install mariadb-server

-- Start service
$ sudo systemctl start mariadb

-- Enable on boot
$ sudo systemctl enable mariadb
```

Increase the number of connections to mariadb from the default 151 to at minimum 2049. In /etc/my.cnf add a max\_connections value.

## **/etc/my.cnf**

```
[mysqld_safe]
max_connections = 2049
```

After this, you will need to create the SHRINE database user and grant it full access:

```
$ mysql -u root

mysql> CREATE USER 'shrine'@'localhost' IDENTIFIED BY 'demouser';
mysql> GRANT ALL privileges ON *.* TO 'shrine'@'localhost';
mysql> \q
```

Sign into MySQL as root and grant the shrine user full access again to all of these databases and their tables:

```
$ mysql -u root
MariaDB [(none)]> GRANT ALL privileges ON *.* TO 'shrine'@'localhost';
```