

Chapter 8.3 - Configuring Query Breakdowns

Breakdown Result Output Types Config

As of SHRINE 1.22.8, it is required to specify the names of result types corresponding to breakdown queries. Their names must match the names of result output types defined in the i2b2 database of every node on your SHRINE network. Your hub admin will supply the right `breakdownResultOutputTypes` for your network. For example, on a network comprised of nodes backed by i2b2 demo VMs, add this section to `shrine.conf` (this section should be under the main `shrine {}` block):

```
shrine {  
  ...  
  
  breakdownResultOutputTypes {  
    PATIENT_AGE_COUNT_XML {  
      description = "Age patient breakdown"  
    }  
  
    PATIENT_RACE_COUNT_XML {  
      description = "Race patient breakdown"  
    }  
  
    PATIENT_VITALSTATUS_COUNT_XML {  
      description = "Vital Status patient breakdown"  
    }  
  
    PATIENT_GENDER_COUNT_XML {  
      description = "Gender patient breakdown"  
    }  
  }  
  
  ...  
}
```

the JSON format for this section is:

```
breakdownResultOutputTypes {  
  <breakdown-result-output-type-name A> {  
    description = <string human-readable-description A>  
  }  
  ...  
  <breakdown-result-output-type-name B> {  
    description = <string human-readable-description B>  
  }  
}
```

note that `breakdownResultOutputTypes` can contain 0 or more child elements.